

# CB-NS370S

## 1U 4-Bay SAS/SATA JBOD Chassis



- Supports SAS/SATA (3Gbps)
- Host Connection by high speed 10Gbps of miniSAS (SFF8088)
- Backplane design for four removable SATA drive trays
- Two quiet hot swap blowers for self-contained ventilation
- Individual key lock of each HDD tray for physical security
- LED indicators for power and activity on each HDD tray
- Environmental Monitoring with Power/FAN/TEMP LEDs and mutable buzzer alarm

## Product Overview

CB-NS370S is a 1U 4 Bay Hot-Swap Serial Attached SCSI (SAS) or SATA Enclosure. It provides users a low cost and high performance external data backup solution. The convenience of miniSAS (SFF8088) interface brings users an easy installation and a fast data transmission experience.

## Specifications

Host Interface	miniSAS (SFF-8088) x1
HDD Interface	SAS/SATA I/II
Data Transfer Rate	SAS 3Gbps; SATA 1.5/3.0 Gbps
Hot-Swap	Both on Host and Device
LED Display	Green – Power on indicator Blue – Busy ( HDD Accessing) indicator
LED Display for Environmental Monitoring	POWER on LED - white FAN normal – green; fail – red (too slow rpm or stop) TEMP normal – green; over 55°C – red
Dimension	(W):48.2cm (H):4.4cm (D):45.3cm
Material	Heavy-duty cold-rolled steel housing, front panel & Plastic tray face
Power Supply	150W Input: 90 – 230 VAC 50- 60 Hz Output: +5V and +12V DC
Cooling Fan	Two sets of 75 x 75 x 28 mm Blowers
O.S. support	OS Independent



### 天弦系統有限公司 Cyberlink Systems Ltd.

香港九龍灣臨樂街 19 號南豐商業中心 7 樓 11 室  
UNIT 11, 7/F., NAN FUNG COMMERCIAL CENTRE,  
19 LAM LOK STREET, KOWLOON BAY, KLN., HONG KONG  
電話 Tel : (852) 2757 0383 傳真 fax : (852) 2757 2198  
網址 WEB URL : <http://www.nas.com.hk>