



天弦系統有限公司
Cyberlink Systems Ltd.



CB-NS360S

1U 4-bay SAS JBOD Chassis, Fail Over support

CB-NS360S is a four Bay Hot-Swap Serial Attached SCSI (SAS) Enclosure. It provides users a low cost and high performance external data backup solution. The convenience of mini SAS interface brings users an easy installation and a fast data transmission experience.

Features

- Supports SAS/SATA (3Gbps)
- Aluminum housing, anodized surface, benefits for cooling and durability
- Backplane design for four removable SATA drive trays
- Two quiet hotswap blowers for self-contained ventilation
- Individual key lock of each HDD tray for physical security
- LED indicators for power and activity on each HDD tray
- Environmental Monitoring with Power/FAN/TEMP LEDs and mutable buzzer alarm.

Specifications

Host Interface	SAS; SATA II (two mini SASX4 connectors)
HDD Interface	SAS; SATA I/II
Data Transfer Rate	SAS 3Gbps; SATA 1.5/3 Gbps
Hot-Swap	Both on Host and Device
LED Display	Green - Power on indicator Blue - Busy (HDD Accessing) indicator
LED Display for Environmental Monitoring	POWER on LED - white FAN normal – green; fail – red (too slow rpm or stop) TEMP normal – green; over 55°C – red (We strongly recommend customers to replace a new fan ASAP after the fan failed)
Dimension	(L):45.3cm (W):48.2cm (H):4.4cm
Material	Anodized Aluminum with Mirror Acrylic plastic front panel & Plastic tray face
Power Supply	150W Input: 90 – 230 VAC 50- 60 Hz Output: +5V and +12V DC
Cooling	Two 75 x 75 x 28 mm Blowers
O.S. support	OS Independent

Package Content

Enclosure x 1
HDD Tray x 4
mini SAS Cable x 1 (Optional)
Power Cord x 1
Manual CD-ROM x1
Hard Disk Drive mounting screw x 16
Key for HDD tray x 2