



天弦系統有限公司
Cyberlink Systems Ltd.



CB-NS760S

Tower 8-bay Multilane SAS/SATA Enclosure

CB-NS760S is an 8 Bay External Hot-Swap SAS/SATA Enclosure. It provides users a flexible solution for SAS or SATA HDD or HBA and high performance external data storage solution for HDTV of 1080i & 1080P Video Editing or any high resolution video platform. This 8 Bay external SAS/SATA JBOD is designed with two convenience of Multilane interface brings users an easy installation and a fast data transmission experience.

Features

- Supports SAS/SATA (3Gbps)
- Aluminum housing, anodized surface, benefits for cooling and durability
- High performance SAS/SATA Backplane design for 8 removable SAS/SATA drive trays
- Built-in fans for self-contained ventilation
- Individual key lock of each HDD tray for physical security
- LED indicators for power and activity on each HDD tray
- Environmental Monitoring with Power/FAN/TEMP LEDs and mutable buzzer alarm.

Specifications

Host Interface	SAS/SATA II (Two Multilane x4 connector)
HDD Interface	SAS / SATA I/II
Data Transfer Rate	SAS 3Gbps & SATA 1.5/3Gbps
Hot-Swap	Both on Host and Device
LED Display	Green - Power on indicator Blue - Busy (HDD Accessing) indicator
LED Display for Environmental Monitoring	POWER on LED - white FAN normal – green; fail – red (too slow rpm or stop) TEMP normal – green; over 55°C – red (We strongly recommend customers to replace a new fan ASAP after the fan failed)
Dimension	(L):23.15cm (W):15.68cm (H):31cm
Material	Anodized Aluminum with Mirror Acrylic plastic front panel & Plastic tray face
Power Supply	300W (High reliability of IPC form-factor) Input: 90 – 230 VAC 50- 60 Hz Output: +5V and +12V DC
Cooling	Four 60 x 60 x 10 mm Cooling Fan (Without any HDD installed, fan don't spin up)
O.S. support	OS Independent

Package Content

Enclosure x 1
HDD Tray x 8
Power Cord x 1
Manual CD-ROM x1
Hard Disk Drive mounting screw x 32
Key for HDD tray x 2