



Desktop 8 Bay

Thunderbolt™ 2 RAID Storage

- Stylish desktop 8 bay Thunderbolt RAID Storage
- Thunderbolt™2 interface with 20Gbps of throughput in both channels
- Supports eight (8) SAS/SATA (6G/3Gbps) HDD Trays
- RAID-on-Chip (ROC) processor
- Support RAID level 0, 1, 10(1E), 3, 5, 6, 50, 60, Single Disk or JBOD
- Individual key lock on each HDD tray for physical security
- Temperature, fan failure LEDs and mutable buzzer alarm

Overview

The CB-NA762TB is the Thunderbolt™2 desktop 8-bay RAID subsystem developed with most up-to-date, 20Gb per second high-speed I/O technology and built with high-performance RAID-on-chip hardware RAID processor and SDRAM memory in support of reliable RAID storage processing, fast delivery, and secure data protection ideal for video editing professionals engaging in high-definition, 2K, 4K, and 3D stereoscopic digital content creation on any demanding configurations for the fastest ever available connection to both Thunderbolt-equipped desktop and laptop computer.

The Versatile Storage for Pro

The CB-NA762TB is thoughtfully designed to have two Thunderbolt ports for daisy-chaining with host, upstream and downstream devices/display for accessible lightning-fast 20Gbps bi-directional data transfers and uninterrupted DisplayPort signal of both high-definition audio and video. Video editing professionals can also choose Thunderbolt PCIe expansion enclosure TurboBox™ to be daisy-chained with CB-NA762TB for adding professional video capture cards to meet editors' requirements on work for best solution.

Easy Maintenance for Real-Time Synchro

The desktop 8-bay RAID subsystem supports plug-n-play and is driver OS-embedded, functioning automatic powering on and off with host through Thunderbolt. The configuration and monitor of CB-NA762TB is rather simple via software on host or web-based GUI by connection to Ethernet port on storage. Through the innovative tech of Thunderbolt on CB-NA762TB, video editors are able to transfer files of between HD and 4K and data backup within only a very short period of time, best and perfect for blazing-fast synchronization of content between devices.

Performance



Specifications

Host Interface •Thunderbolt™2 •20Gbps Bi-directional	
Controller & RAID Feature •RAID-on-Chip Processor •Supports RAID Level 0, 1, 10(1E), 3, 5, 6, 30, 50, 60, Single Disk or JBOD •Online Array Roaming •Online Capacity Expansion and RAID Level Migration Simultaneously •SDRAM •Multiple RAID Selection •Online RAID Level/Stripe Size Migration •Greater than 2TB Capacity per Disk Drive Support	
Storage •Supports up to 8 SAS/SATA 3Gbps or 6Gbps 3.5" HDDs (Hard Disks Sold Separately) •Stylish Aluminum Housing with Solid Metal Structure+Thunderbolt Port for Daisy-chain up to 6 Devices •Individual Key lock of each HDD tray for physical security	
Monitors/Indicators •Web-based GUI RAID Manager for Remote Management •SNMP Support for Remote Manager •Over Temperature LED •SMTP Support for Email Notification •FAN fail LED •HDD fail LEDs	
Fan Cooler •Two 80x80x25mm •Hot-Swappable	
Power Supply •Server-grade 300W Single Power Supply •Universal: 100-240VAC, 50/60Hz •Low-noise Design	
Environmental Requirements •Operation Temperature: 5°C ~ 50°C •Operation Humidity: 10% ~ 80%, non-condensing •Storage Temperature: -20°C ~ 70°C •Storage Humidity: 5% ~ 95%	
Dimension •231(D) x 156(W) x 365(H) mm •9.1(D) x 6.1(W) x 14.4(H) inch	
Operating System •Mac OS X 10.6.x/10.7.x/10.8.x / Mavericks (Driver was integrated by Apple OS X Mountain Lion/OS X Mavericks)	
Scalability •Thunderbolt port for daisy-chain up to 6 devices	